



**NOTES:**

1. DOUBLE FUSION HOT WEDGE SEAM IS THE MOST COMMON SEAMING TECHNIQUE USED TO SEAM TOGETHER.
2. AIR PRESSURE OR VACUUM TESTING ARE THE TWO METHODS TO TEST A SEAM DOUBLE FUSION.
3. REFER TO THE QUALITY CONTROL CONSTRUCTION MANUAL FOR THE SPECIFIC TEST METHOD.

**DISCLAIMER**

THIS DRAWING IS THE PROPERTY OF AQUATAN (PTY) LTD AND CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT, IN WHOLE OR IN PART, BE REPRODUCED OR DIVULGED, COPIED OR DISTRIBUTED IN ANY WAY OR FOR ANY PURPOSE WHATSOEVER WITHOUT WRITTEN PRIOR AUTHORIZATION FROM AQUATAN (PTY) LTD. THIS DRAWING AND ALL INFORMATION, DIMENSIONS AND SPECIFICATIONS THEREON ARE FOR INFORMATION PURPOSES ONLY. THIS IS NOT A DRAWING ISSUED FOR CONSTRUCTION. AQUATAN (PTY) LTD ASSUMES NO LIABILITY IN ANY WAY WHATSOEVER FOR THE CORRECTNESS OF THE DRAWING OR ANY INFORMATION, SPECIFICATIONS AND DIMENSIONS ON THE DRAWING AND ANY RELIANCE THEREON BY ANY THIRD PARTY.

REVISIONS		BY
No.	DESCRIPTION	
--	--	--

**AQUATAN**  
LINING SYSTEMS - THE TOTAL SOLUTION

10 Diesel Road, Isando 1600  
PO Box 633, Isando 1600, South Africa  
Tel: +27 (0) 11 974 5271 - Fax: +27 (0) 11 974 4111  
E-mail: aqua@aquatan.com - www.aquatan.com

CLIENT  
.....

TITLE  
TYPICAL DOUBLE FUSION SEAM  
DETAIL

REF. DRG.  
.....

DRAWN	DATE	SIGN
T. MANELI	23/03/2015	
CHECKED	DATE	SIGN
P. MEYER		
SCALE	NOT TO SCALE	
DWG. No.	STD - 3	REV. 01
COPYRIGHT AQUATAN LINING SYSTEMS (PTY) LTD 2001		A4